



SR-15 E3 CQB MOD 2 M-LOK P/N: 31952

Barrel 11.5"(29 cm) 1:7 Twist, Hammer Forged, Chrome Lined Caliber 5.56 mm NATO Weight 6.25 lbs (2.83 kg)

SR-25 E2 ADVANCED COMBAT CARBINE M-LOK

Caliber 7.62 mm NATO / .308 Win

Length | 35.75"(91 cm) to 39.5"(100 cm)

Weight | 8.4 lbs (3.8 kg)

Barrel 16"(40 cm) 5R Cut, Chrome Lined 1:10 Twist

Length 29"(73.6 cm) to 32"(81.3 cm) P/N: 31963 Upper Receiver Kit

AMBIDEXTROUS CONTROLS KESS MULTI LUG IMPROVED ES BOLT M-LOK ACCESSORY MOUNTING SYSTEM

2 STAGE MATCH TRIGGER

QDC QUICK DISCONNECT



SR-15 E3 CARBINE MOD 2 M-LOK

SR-15 E3 CARBINE MOD 2 M-LOK P/N: 31946

Barrel 14.5"(37 cm) 1:7 Twist, Hammer Forged, Chrome Lined Caliber 5.56 mm NATO Weight | 6.4 lbs (2.9 kg)

Length 32"(81 cm) to 35"(89 cm)

P/N: 31949 Upper Receiver Kit

SE33 MULTI LUG IMPROVED E3 BOLT

M-LOK ACCESSORY MOUNTING SYSTEM

2 STAGE MATCH TRIGGER

QDC QUICK DISCONNECT



P/N: 31900

HAMMER FORGED

AMBIDEXTROUS CONTROLS

SE32 MULTI LUG IMPROVED E3 BOLT

 $\left(\frac{1}{2}\right)$ 2 STAGE MATCH TRIGGER

QDC QUICK DISCONNECT



AMBIDEXTROUS CONTROLS

MULTI LUG IMPROVED E3 BOLT

M-LOK ACCESSORY MOUNTING SYSTEM

 $\left(\frac{1}{2}\right)$ 2 STAGE MATCH TRIGGER

QDC QUICK DISCONNECT

SR-25 E2 ACC M-LOK

SR-25 E2 APC M-LOK



AMBIDEXTROUS CONTROLS

MULTILUG IMPROVED E2 BOLT

R CUT RIFLED BARREL

M-LOK ACCESSORY MOUNTING SYSTEM

2 2 STAGE MATCH TRIGGER

QDC QUICK DISCONNECT

Barrel 16"(40 cm) 5R Cut 1:10 Twist Caliber 7.62 mm NATO / .308 Win

Weight 9 lbs (4.1 kg) Length | 35.75"(91 cm) to 39.5"(100 cm)

SR-25 E2 ADVANCED PRECISION CARBINE M-LOK P/N: 31955

2 STAGE MATCH TRIGGER

5R CUT RIFLED BARREL

AMBIDEXTROUS CONTROLS

MULTILUG IMPROVED E2 BOLT

QDC QUICK DISCONNECT COUPLING

SR-25 E2 APR M-LOK



SR-25 E2 APR ADVANCED PRECISION RIFLE P/N: 31961

Barrel | 20"(51 cm) 5R Cut 1:10 Twist Caliber 7.62 mm NATO / .308 Win

Weight 10.5 lbs (4.8 kg)

SR-15 E3 MOD 2 M-LOK

Caliber 5.56 mm NATO

Weight 6.55 lbs (2.97 kg)

P/N: 31296 Upper Receiver Kit

Length | 33.5"(85.09 cm) to 36.5"(92.7 cm)

Barrel 16"(40 cm) 1:7 Twist, Hammer Forged, Chrome Lined

Length | 39.75"(101 cm) to 43.5"(110.5 cm)



AMBIDEXTROUS CONTROLS MULTILUG IMPROVED E2 BOLT

M-LOK ACCESSORY MOUNTING SYSTEM

2 2 STAGE MATCH TRIGGER

QDC QUICK DISCONNECT COUPLING

SR-30 M-LOK

P/N: 31970



SR-15 E3 LIGHT PRECISION RIFLE MOD 2 M-LOK P/N: 31973

Barrel 18"(45 cm) 1:7 Twist, Stainless Steel

Length | 35.25"(89.53 cm) to 38.5"(97.8 cm)

Caliber 5.56 mm NATO

Weight 7.4 lbs (3.35 kg)

P/N: 32309 Upper Receiver Kit

AMBIDEXTROUS CONTROLS SE33 MULTI LUG IMPROVED E3 BOLT

M-LOK ACCESSORY MOUNTING SYSTEM

 $\left(\frac{1}{2}\right)$ 2 STAGE MATCH TRIGGER

QDC QUICK DISCONNECT COUPLING

KAC M-LOK PRODUCTS

SR-15 E3 MOD 2 M-LOK SERIES

and is free-floated inside a URX4 M-LOK handguard. An improved E3 round-lug bolt are equally adept at putting rounds on target past 800 meters or rapid multi-shot engagement design both enhances function and increases bolt life far beyond the industry standard. The at close range, with a barrel and bolt life to support the training regimen necessary to master ambidextrous bolt release, selector lever, and magazine release offers left-handed users the these skills. An ambidextrous bolt release, selector, and magazine release offer the leftergonomic advantages inherent to AR15-based controls. The drop-in two-stage trigger serves handed user the ergonomic advantages inherent to AR15 based controls, as well as giving double duty as an aid to precision marksmanship while enabling surgical speed shooting at right-handed users alternate methods of manipulation to increase efficiency of movement. close range. The 5.56 mm 3-Prong Flash Eliminator interferes with propellant gas combustion The drop-in 2-stage trigger serves double duty as an aid to long range precision marksmanship forward of the muzzle to significantly reduce flash signature, will not ring upon firing or when while enabling surgical speed shooting at close range. A 7.62 QDC Flash Suppressor

SR-30 M-LOK SERIES

an 11.5" 5.56 mm SBR, for a significantly more transportable and maneuverable firearm. The QDC handguards, but are fully compatible with other handguards that are built to the published technical compatible Flash Hider will mount any of the KAC 7.62 mm QDC suppressors. The SR-30 has 99% data package. Construction material selected to match application; aluminum for weight reduction, parts compatibility with the SR-15, requiring only a dedicated barrel and muzzle device. Seamlessly steel for high strength and durability. transition from subsonic ammunition to supersonic with nothing more than a change of the magazine.

SR-25 E2 MOD 2 M-LOK SERIES

The SR-15 E3 Mod 2 series' 5.56 mm NATO barrel is manufactured for military grade durability, The SR-25 E2 series is the latest evolution of the dual role 7.62 mm NATO Carbine and Rifle. Each struck, and is compatible with the Knight's line of 5.56 mm QDC Signature Reduction Devices. reduces flash and ground disturbance, and supports KAC QDC Signature Reduction Devices.

KAC M-LOK ACCESSORIES SERIES

WWW.KNIGHTARMCO.COM

The SR-30 E3 Mod 2 takes advantage of the .300 BLK, offering a 9.5" barrel that is as capable as KAC M-LOK accessories are primarily designed to optimally interface with the URX4 series of



KAC M-LOK ACCESSORIES

SR-30 M-LOK

Weight 6.2 lbs (2.81 kg)

P/N: 32310 Upper Receiver Kit

M-LOK SCOUT LIGHT MOUNT P/N: 31906

The KAC M-LOK mount for SureFire M300 and M600 Scout Lights is a lightweight, direct-attach mounting platform that replaces the OEM mount. The mount can be positioned to place the light close to the handguard at any position from 1:30 to 11:30 in relation to the top 12:00 rail. Aluminum construction.

Barrel 9.5"(24 cm) 1:7 Twist, Chrome Lined

Length 27.5"(69.2 cm) to 30.75" (70.47 cm)

Caliber 300 Blackout (7.62 x 35 mm)



accessories. Designed specifically for the M-LOK URX 4 handguard, M-LOK URX 4 rail at the 45 degree position on the right or left hand sling swivels (sold separately). this rail section is also compatible with any other rifle handguard side. Intended to be used in conjunction with KAC Rail Mounted that has an M-LOK interface. Aluminum construction.



M-LOK 5-SLOT RAIL P/N: 31912 M-LOK MICRO FRONT SIGHT P/N: 31896

Offset Folding Rear Sight (P/N 30878). This sight is compatible with other handguards that feature an M-LOK interface at 45 degrees from the top rail.



The KAC M-LOK Skeletonized Barrier Stop eliminates all unnecessary weight while still being robust enough for hard-use. The serrated front edge will bite into most surfaces at any angle of contact. Steel construction.



This KAC M-LOK Accessory Rail is 3" in length and provides a The KAC M-LOK Offset Flip Up Front Micro Sight, with finger— The KAC M-LOK Sling Mount attaches quickly and securely to an 5 slot section of MIL-STD-1913 rail for the addition of tactical adjustable sight post, is designed specifically for attachment to the M-LOK interface. The sling mount is compatible with push button

ITAR International Traffic in Arm Regulations

Email: salesteam@knightarmco.com

Phone: 321.607.9900

Fax: 321.268.1498

701 Columbia Blvd.

Titusville, Florida 32780

www.knightarmco.com

Company is an ISO 9001 Certified Company. The products, product specifications, nomenclature, and availability of all items

ITAR STATEMENT: These item(s) are firearm or defense related goods. Export of the goods described herein is strictly prohibited without a valid export license issued by the US Department of State, Directorate of Defense Trade Controls as prescribed in International Traffic in Arms Regulation (ITAR), code of federal regulations, Title 22, Parts 120- 130.

